

PRODUCT SPECIFICATIONS

550 ROOF LOUVER

1.1 MATERIALS:

1.1.1 Aluminum Alloys: Conform to ASTM B209.

Base: 0.019" Aluminum Coiled Sheet.

Collar: 0.019" Aluminum Coiled Sheet.

Pan: 0.019" Aluminum Coiled Sheet.

Bracket: 0.061" Aluminum Coiled Sheet.

1.1.1 Plastic Polymers:

Collar: Custom blended, high impact co-polymer with UV stabilization additives.

1.1.3 Screen: 10 mil, 8x8 mesh perma-coated Aluminum Screen.

1.1.4 Paint: Factory applied baked on Valspar Super Flex.

1.2 MISCELLANEOUS:

1.2.1 Description: Pan-style, self-flashing roof mounted attic exhaust vent. Features a weather-tight collar, seamed to the base flashing and large nailing flange. Screen is securely riveted in place and covers the entire vent opening. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

1.2.2 Color: Available in BROWN, WHITE, BLACK, WEATHERED BRONZE, and MILL finish.

1.2.3 Net Free Area: 50 square inches per unit.

1.2.4 Dimensions: Overall – 15-3/8" x 16-3/8" x 4", Hole Size – 9".

1.2.5 Packaging: Packaged 6 to a carton. UPC labels are affixed to each vent and carton.

1.2.6 Approvals: Texas Department of Insurance "Windstorm" Approved –
Product Evaluation Report No.: RV-109.

1.2.7 Other: CSA approved for Canada.



P.O. Box 519
Jacksonville, AR 72078
1-800-643-5596 phone
501-982-1258 fax

Revised on 11/14/2019