





- 2³/₄" wide continuous strip.
- 3³/₄" wide continuous strip.
- 1" x 1/8" louvered openings.
- 1" x 1/8" louvered openings.
- 23/8" wide continuous strip.
- 1" $x^{1/8}$ " louvered openings.
- Instead of two ³/₈" channels, there is only one with the other edge turned up 90 degrees to allow for easier installation.

Continuous Soffit Vents

- All-aluminum construction.
- Available in 8-foot sections and can be cut at 2-foot intervals.
- Mounting flange is recessed 3/8" for soffit board.

Model	Length	Width	NFA	Ctn. Qty.	Ctn. Wt. (lbs)
105	8'	2¾"	72 in²	36	21.6
105 Copper	8'	2¾"	72 in²	15	28.5
140	8'	3¾"	88 in²	36	28.4
190	8'	23/8"	72 in²	36	22.3



Cirk-L-Vents

















- All-aluminum construction.
- 18x16 aluminum screen attached for added protection (except for D-16).
- Unique "eyebrow" designed louvers provide maximum ventilating capacity with superior weather protection.
- Prevents paint peeling by removing moisture from wall cavities.
- Provides an outlet for air movement in small confined spaces.
- Easy installation (drill and pop in).

Model	Description	Overall Size	Hole Size	NFA	Inner Ctn. Qty.	Ctn. Qty.	Ctn Wt. (Ibs)
L-38	Screen & Louvers	3"	21/2"	1.63 in ²	6	72	2.8
C-25	Screen only	33/16"	21/2"	2.34 in ²	6	72	2.3
P-18	Screen & Louvers	1"	3/4"	0.20 in ²	6	72	0.7
D-16	Louver only	1"	3/4"	0.44 in ²	6	72	0.5
CV-4	Screen & Louvers	41/2"	4"	3.00 in ²	_	36	2.9
CV-4 Copper	Screen & Louvers	41/2"	4"	3.00 in ²	_	36	7.2
CV-3	Screen & Louvers	31/2"	3"	2.57 in ²	6	72	3.5
CV-2	Screen & Louvers	21/4"	2"	1.50 in ²	6	72	2.0
CV-1	Screen & Louvers	11⁄4"	1"	0.23 in ²	6	72	0.7

